

OLYMPUS[®]

Your Vision, Our Future

Surgical Tissue Management System

USG-400

Ultrasonic Generator



Ultrasonic Generator

USG-400

Main features

USG-400 is a universal platform that supports

- THUNDERBEAT. Exclusively delivering both ultrasonic and bipolar energy for reliable vessel sealing and the fastest tissue cutting.*
- SONICBEAT. Delivering ultrasonic energy for the simultaneous cut and coagulation of tissue.
- Conventional monopolar and bipolar instruments for cut and coagulation.*
- Conventional TUR or Saline TUR instruments for urologic and gynecologic resection.*

* When combined with Olympus ESG-400, electro-surgical generator.

USG-400 Features and Benefits

- Graphical User Interface for intuitive operation, ease of use, and rapid troubleshooting.
- Instrument recognition and automatic application of default settings for ease of use.
- Hand switch and foot switch activation options to meet each surgeon's individual preferences.
- Automatic mist and smoke evacuation to maintain a clear laparoscopic view reducing delays associated with compromised visualization.**
- A dedicated cart for transportation and storage.

** When combined with Olympus UHL series insufflator.

Dimensions



USG-400 and ESG-400 (optional) installed on TC-E400

USG-400 Specifications

Power Supply	Voltage	120/220 – 240 V AC
	Voltage fluctuation	Within $\pm 10\%$
	Frequency	50/60 Hz
	Frequency fluctuation	Within ± 1 Hz
	Input	360 VA
	Fuse rating	4 A, 250 V
	Fuse size	$\phi 5 \times 20$ mm
Size	Dimensions	375 (W) \times 156 (H) \times 480 mm (D)
	Weight	9 kg
Classification (medical electrical equipment)	Type of protection against electric shock	Class I
	Degree of protection against electric shock	CF type
	Degree of protection against explosion	The ultrasonic generator should be kept away from flammable gases.
Output	Applicable instrument	THUNDERBEAT* SONICBEAT
	ON/OFF operation	Footswitch Handswitch
	Output setting	Setting possible in the Set Screen displayed on the touch panel.
	Frequency	47.0 kHz

* When combined with ESG-400.

TC-E400 Energy Cart Specifications

Dimensions	515 (W) \times 1047 (H) \times 715 (D) mm
Shelf Width	378 mm
Weight	38 kg
Load Capacity (when equally distributed)	Equipment shelf 40 kg* ¹
	Foot switch shelf 20 kg
	Drawer 5 kg
Casters	4 \times $\phi 125$ mm dia., with brakes on all the casters.

*¹ Do not place an instrument with a larger footprint than the shelf plate on the EPF Cart.

Specifications, design and accessories are subject to change without any notice or obligation on the part of the manufacturer.

OLYMPUS[®]

OLYMPUS MEDICAL SYSTEMS CORP.
Shinjuku Monolith, 2-3-1 Nishi-Shinjuku, Shinjuku-ku, Tokyo 163-0914, Japan

For a complete listing of sales and distribution locations visit:
www.olympus.com